

PE 555



UV-RESISTANT, WATERPROOF STUCCO MASKING TAPE

TYPICAL APPLICATIONS

- For masking surfaces during stucco application and painting
- Can also be used for surface protection, color-coding, splicing and seaming on pipe-fitting covers

PRODUCT FEATURES

- UV-resistant
- Excellent adhesion and tearability
- Removes cleanly
- Waterproof

CONSTRUCTION

Overall Grade/Function: Multipurpose

Backing: Red polyethylene film

Adhesive: Synthetic rubber

STANDARD WIDTH(S)

48 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	27 lbs/in width	47.3 N/10 mm
Adhesion to Stainless Steel	92 oz/in width	10.07 N/10 mm
Thickness	9.0 mils	0.23 mm
Elongation	94%	94%
Service Temperature Range	32 F to 160 F	0 C to 71 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

